FIG. 2


OBTAIN OR CREATE ORIGINAL DIGITAL SIGNAL OR IMAGE
ESTIMATE ROUGH OFFSET AND RMS NOISE
CHOOSE N OR N-BIT IDENTIFICATION WORD, E.G. 32
GENERATE N-BIT IDENTIFICATION WORD
GENERATE OR SYNTHESIZE N "RANDOM" INDEPENDENT SIGNALS WITH ROUGHLY GAUSSIAN DISTRIBUTION ABOUT SOME MEAN VALUE, WHERE SIGNALS HAVE EQUAL EXTENT AND DIGITAL SPACING OF ORIGINAL DIGITAL SIGNAL OR IMAGE
APPLY DIGITAL FILTER WHICH ATTENUATES BOTH LOW AND HIGH FREQUENCIES, LEAVING MIDDLE-RANGE FREQUENCIES LARGELY INTACT
CONDENSE N RANDOM SIGNALS TO A LOWEST ACCEPTABLE BIT VALUE IF MEMORY OR STORAGE SPACE IS AT A PREMIUM
ADD ALL RANDOM IMAGES TOGETHER WHICH HAVE A CORRESPONDING '1' IN THEIR ASSOCIATED BIT-PLACE-VALUE OF THE N-BIT IDENTIFICATION WORD, CALL THIS THE BASE COMPOSITE SIGNAL OR IMAGE
EXPERIMENT VISUALLY WITH GAIN AND GAMMA APPLIED TO BASE COMPOSITE SIGNAL OR IMAGE, ADDING THIS TO ORIGINAL DIGITAL SIGNAL OR IMAGE, AND DETERMINING THE ACCEPTABLE PERCEIVED NOISE LEVEL
APPLY FOUND GAIN AND GAMMA TO BASE COMPOSITE, ADD TO ORIGINAL, THEN CALL THIS THE DISTRIBUTABLE SIGNAL OR IMAGE
STORE AWAY AND SECURE ORIGINAL SIGNAL OR IMAGE, ALONG WITH N-BIT IDENTIFICATION WORD AND THEN RANDOM SIGNALS
SELL OR DISTRIBUTE THE DISTRIBUTABLE SIGNAL OR IMAGE

FIG. 3


OBTAIN DIGITAL OR NON-DIGITAL COPY OF SUSPECT SIGNAL OR IMAGE
DIGITIZE IF NOT ALREADY DIGITAL
CUT AND MASK PORTION OF SIGNAL OR IMAGE BELIEVED TO BE SUSPECT (ONLY IF ENTIRE SIGNAL OR IMAGE IS NOT SUSPECT)
PROCURE ORIGINAL DIGITAL SIGNAL OR IMAGE AND CUT AND MASK TO ROUGHLY THE SAME LOCATION OR SEQUENCE
VISUALLY RESCALE AND REGISTER THE CUT-OUT SUSPECT SIGNAL TO THE CUT-OUT ORIGINAL SIGNAL
RUN THROUGH SEARCH PROGRAM WITH MEAN SQUARED ERROR AS CRITERIA AND X OFFSET, Y OFFSET, AND SCALE AS THE THREE VARIABLES
APPLY X OFFSET, Y OFFSET, AND SCALE TO CUT-OUT SUSPECT, THEN RESAMPLE ONTO EXACT GRID AND CUT-OUT OF ORIGINAL SIGNAL
RUN THROUGH SEARCH PROGRAM WITH MEAN SQUARED ERROR AS CRITERIA AND DC OFFSET, GAIN, AND GAMMA AS THE THREE VARIABLES; APPLY TO SUSPECT
SUBTRACT ORIGINAL FROM SUSPECT, GIVING DIFFERENCE SIGNAL OR IMAGE
STEP THROUGH ALL N RANDOM INDEPENDENT SIGNALS, MASKED AS ORIGINAL AND CROSS-CORRELATED WITH DIFFERENCE SIGNAL IN IMMEDIATE NEIGHBORHOOD OF REGISTRATION POINTS
FIND 0 AND 1 LEVEL BY AVERAGING FIRST FOUR 0101 CODE VALUES
ASSIGN EITHER A 0 OR A 1 TO EACH CROSS-CORRELATION RESULT DEPENDING ON PROXIMITY TO THE AVERAGES OF PREVIOUS STEP
CHECK RESULT AGAINST SECURED IDENTIFICATION NUMBER
PROSECUTE IF IT MATCHES? OR AT LEAST SEND A NASTY LETTER DEMANDING RECOMPENSE

FIG. 4


COMPUTER
102
106
104
100
EXPOSE AND STEP

FIG. 1


DIGITAL NUMBER (SIGNAL LEVEL)
12
8
4
0
0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
SAMPLE NUMBER (INDEX)
'4-BITS'

FIG. 5


CODE WORD
(e,g. 01101001)
INPUT
SIGNAL
REAL-TIME
ENCODER
IDENTIFICATION-
CODED OUTPUT
SIGNAL
KEY DATA
(OPTIONAL)

FIG. 6


ANALOG
NOISE
SOURCE
222
202
206
A/D
224
204
FIRST
SCALER
208
LOOKUP
TABLE
210
226
SECOND
SCALER
214
220
MEMORY
INPUT
ADDER
SUBTRACTER
OUTPUT
218
232
212
234
230
01011000
216


NOISE SOURCE
NOISE STORE
206
CODE 1
CODE 2-N
242
202
REAL TIME ENCODER
INPUT
OUTPUT
234
0 0 1 0 0 0 0 0
0 0 1 0 0 0 0 1
0 0 1 0 0 0 1 0
0 0 1 0 0 0 1 1
0 0 1 0 0 1 0 0
0 0 1 0 0 1 0 1
0 0 1 0 0 1 1 0
0 0 1 0 0 1 1 1
0 1 0 1 1 0 0 0
1ST THROUGH NTH CODE WORDS

FIG. 7

FIG. 8


248
202
REAL TIME ENCODER
A/D
A/D
OUTPUT
NOISE
CODE
NOISE SOURCE
250
RESET
SYNC DETECTOR
INCREMENT
0 0 1 0 0 0 0 0
0 0 1 0 0 0 0 1
0 0 1 0 0 0 1 0
0 0 1 0 0 0 1 1
0 0 1 0 0 1 0 0

FIG. 9A



FIG. 9B



FIG. 9C



FIG. 10



FIG. 11


STANDARD NOISE SIGNATURE
504
READ OUT AT125% NORMAL RATE
604
PITCH CHANG ED NOISE SIGNAL
606
599
600
INPUT AUDIO SIGNAL
SIGNAL–PITCH CANCELLED NOISE SIGNAL
608
602
TIME AVERAGED POWER SIGNAL P_{SIG}
TIME AVERAGED POWER SIGNAL P.C. NOISE SIGNAL P_{S-PCN}
610
POWER DIFFERENCE SIGNAL
$P_{S-PCN} - P_{SIG} - P_{OUT}$
612
613
614
CASE 1:
0S 5S 10S 15S
616
CASE 2:
0S 5S 10S 15S
4 SECOND BEATS
618

FIG. 12


624
AUDIO VALID COUNTER
FLAG VALID SIGNAL
508
600
SIGNAL ONE
599
BEAT DETECTION
622
.05S DIGITAL DELAY
599
.05S DIGITAL DELAY
620
.05S DIGITAL DELAY
.05S DIGITAL DELAY
502
DETECTION FLAG

Figure 13



700



Encryption/Scrambling
Routine # 28 ,702



704 Pseudo-Random Master Snowy Image
(Scaled Down and Added to Frame 12183)

Figure 14



720, Mean-Removed Histograms of Difference Signal and Known Embedded Code Signal



722, Mean-Removed Histograms of First Derivatives (or scaler gradients in the case of an Image)

Figure 15


Step Z Frames, 750
Render Logo Frame, 700
Encrypt/Scramble, 702
Output Master Snowy Image Frame, 704
High Brightness Master Snowy Movie, 752
MPEG, 754
Difference, 758
"Cheap Master Snowy Movie", 760
Compressed Master Snowy Movie, 756
Original Movie, 762
Scale Down, 764
Add, 766
Distributable Movie, 770
Side-by-Side Viewing, 768
Original Movie, 762

Figure 16


... Joe's Image...
00110101101110100101010...
Header, 800
Data Stream, 802


Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image
Joe's Image

Figure 17



Universal Empirical Data Format

Figure 18



Supra-radial Knots, 850



Radial Knots, 852

854, One basic concept of the knot is an overlapping of one strand of finite width over another strand

864, Another basic concept is the symetric weaving of overlaps

Figure 19



866, Quest for Mosaiced Knot Patterns which "Cover" and are Coextensvie with Original Image;

All elemental knot patterns can convey the same information, such as a signature, or each can convey a new message in a steganographic sense

Figure 20



876, 2-D brightness of phase-only filtered ring is similar to the above brightness pattern rotated about central point of ring :



Figure 21 A

C	2C	C
2C	4C	2C
C	2C	C

where C = 1 / 16

Elementary Bump, 900
(Defined grouping of pixels with weight values)



Example of how elementary bumps, 900, would be assigned locations in an image, and those locations would be associated with a corresponding bit plane in the N-bit word, here taken as N=8 with indexes of 0-7. One location, associated with bit plane "5", has the overlay of the bump profile depicted.

FIG. 21B

Figure 22


Digital Image Taken of Customer, 940
Computer, 942, Processes New Encoded Image
Prints Processed Image onto Plastic Card
Barcode ID and/or Text, 952
Optional Position Fiducials, 954
Personal Cash Card, 950

Figure 23



Low Cost Point-of-Sale Optical Reader, 958

Contains rudimentary optical scanner, memory buffers, communications devices, and microprocessor

Consumer merely places card into window and can, at their pre-arranged option, either type in a Personal Identification Number (PIN, for added security) or not. The transaction is approved or disapproved within seconds.

Figure 24



Original Digital Image with Barcode and Fiducials Added, 970



Computer generates Master Snowy Image 972, which is generally orthogonal to Original Image at left



Combined to form Personal Cash Card, 950

Figure 25 Typical Transaction Steps

1. Reader scans images on card, stores in memory, extracts persons ID
2. Optional: User keys in PIN number
3. Reader calls central account data network, handshakes
4. Reader sends ID, (PIN), merchant information, and requested transaction amount to central network
5. Central Network verifies ID, PIN, Merchant info, and account balance
6. If OK, Central Network generates twenty four sets of sixteen distinct random numbers, where the random numbers are indexes to a set of 64K orthogonal spatial patterns
7. Central Network transmits first OK, and the sets of random numbers
8. Reader steps through the twenty four sets
   - 8A. Reader adds together set of orthogonal patterns
   - 8B. Reader performs dot product of resultant pattern and card scan, stores result
9. Reader transmits the twenty four dot product results to Central Network
10. Central Network checks results against master
11. Central Network sends final approval or denial
12. Central Network debits Merchant Account, credits Card account

Figure 26 The Negligible-Fraud Cash Card System



A basic foundation of the cash card system is a 24 hour information network, where both the stations which create the physical cash cards, 950, and the point-of-sales, 984, are all hooked up to the same network conitnuously


1002
1006
HO
1012
INTERNET
WEB SITE
DEVELOPMENT TOOL
1008
WWW SITE
1004
1006
HO
1010
BROWSER
WWW SITE

FIG. 27

Fig. 28

Figure 29



Non-harmonic spatial frequencies along the 45 degree axes, giving rise to a weave-like cross-hatching pattern in the spatial domain

Figure 30



Non-harmonic concentric circles in UV plane, where phase hops quasi-randomly along each circle, giving rise to pseudo random looking patterns in the spatial domain

Figure 31A



Phase of spatial frequencies along forward 45 degree axes, 1008

Phase of spatial frequencies along backward 45 degree axes, 1010

FIG. 31B

Figure 32A



Phase of spatial frequencies along first concentric ring, 1012

FIG. 32B

Phase of spatial frequencies along second concentric ring 1014

FIG 32C

Phase of spatial frequencies along third concentric ring, 1016

Figure 33A



Angle A 1018

FIG. 33B



Angle B 1020

FIG. 33C



Power profile along Angle A, as normalized by its own moving average; only a minimal amount exceeds threshold, giving a small integrated value 1022

FIG. 33D



Power profile along Angle B, as normalized by its own moving average; this finds strong energy above the threshold 1024

FIG. 33E



As angle is swept from 0 to 90, 45 degrees has highest energy > threshold 1026

0 degrees 45 degrees 90 degrees

Figure 34A



Radius A, 1028

FIG. 34B



Radius B, 1030

FIG. 34C



Power profile along circle at radius A, 1032



Power profile along circle at raidus B, 1034

FIG 34D

FIG. 34E



Total integrated power above threshold, as function of radius 1038

Figure 35A



Scale = A; add all power values at the "known" frequencies, 1042

FIG. 35B



Scale = B; add all power values at the "known frequencies, 1044

FIG. 35C



"Scaled-kernel" based matched filter; peak is where the scale of the subliminal grid was found, 1046

Figure 36A



Arbitrary Original Image, 1050, in which subliminal graticules may have been placed

FIG. 36B



"Column scan", 1052 is applied along a given angle through the center of the image

FIG. 36C



FIG. 36D

Magnitude of Fourier Transform of scan data, 1060